



30 CUBIC FOOT CHAMBER

AN UNSURPASSED RH CONTROL OF $\pm 0.5\%$.

Parameter's test chambers are designed to accurately produce temperature and humidity conditions required for applications including stability studies, package testing, TAPPI, MIL-SPEC, and vapor transmission. The 30 cu. ft. chamber features our unique humidity control system, enabling the user to attain unsurpassed levels of RH/temperature control and uniformity.

Applications for this unit include diverse industries, such as pharmaceutical development and manufacturing, electronic components, food, semiconductor, paper and pulp, and anywhere precise humidity control and temperature replications are required.

The interior chamber of the unit is constructed of a very durable, corrosion resistant 316 stainless steel. Low watt density heaters are used that also contribute to the unit's longer life.

Depending on the application, the chamber airflow can be factory configured from the standard horizontal flow to a vertical flow. Additional options include extended ranges, chart recorders, outer door window, or clear inner door with optional iris opening.

Specifications

SERIES 9130

Relative Humidity Range: 10 to 95%
(limited by a 4° dew point)

Relative Humidity Constancy: $\pm 0.5\%$

Relative Humidity Uniformity: $\pm 1.0\%$

Temperature Range: 5 to 85°C

Temperature Constancy: $\pm 0.2\%$

Temperature Uniformity: $\pm 0.2\%$

UTILITIES

220v, 20.5 FLA, 1 phase, 60 Hz

220v, 12 FLA, 1 phase, 50 Hz

Higher voltages are also available

Refrigerant: R-134A

(non-ozone depleting gas)

EXTERNAL CHAMBER DIMENSIONS

53.5" w x 36" d x 79" h (nominal)

INTERNAL CHAMBER DIMENSIONS

34.5" w x 28.45" d x 52.5" h (nominal)

WEIGHT


750 lbs.

SHIPPING WEIGHT

1000 lbs

RH VARIABLES	OURS	THEIRS
TOTAL	$\pm 2.5\%$	$\pm 6.0\%$
CONTROL CONSTANCY	$\pm 0.5\%$	$\pm 2.0\%$
CHAMBER UNIFORMITY	$\pm 1.0\%$	$\pm 2.0\%$
SENSOR ACCURACY	$\pm 1.0\%$	$\pm 2.0\%$

Extremely Precise Control
Low Energy Requirements
Low Maintenance



Benefits

- Extremely stable and uniform environment
- Maintains superior constancy and uniformity
- Security and safety
- Equipment longevity; corrosion resistant
- Ease of operation

Features

- RH control constancy of $\pm 0.5\%$
- Temperature control constancy of $\pm 0.2^{\circ}\text{C}$
- Multiple safety cut-offs
- 316 stainless interior chamber
- User-friendly and unit-specific digital controller

SmartPad Microprocessor

Parameter's SmartPad microprocessor controller is a user-friendly system that provides optimum accuracy and control. The SmartPad is equipped with direct readings in both temperature and humidity. It features 60-segment programming for automatic cycling and ramping and soaking excursions. High-low or deviation alarms and digital communications ports are standard features.

All Parameter equipment is exhaustively tested at your specified condition prior to shipping to ensure trouble-free operation.

